



TRACTOR TUG / REMOLCADOR

SHIPOWNER: K & K INTERNATIONAL B.V

CARACTERISTICAS PRINCIPALES

| | |
|-----------------------|----------|
| Eslora total | 31,00 m. |
| Eslora entre p.p. | 28,65 m. |
| Manga de trazado | 12,00 m. |
| Puntal | 5,40 m. |
| Calado sobre patines | 5,90 m. |
| Calado sobre quilla | 3,20 m. |
| Tracción a punto fijo | 70 Tons. |

Tripulación 7 hombres

Tanques Fuel Oil 175 m³

PROPULSION

3 propulsores 2000 BHP, 3 toberas-timón Schottel, 2 a proa y 1 a popa

MAIN CHARACTERISTICS

| | |
|--------------------|----------|
| Length o.a | 31.00 m. |
| Length between pp. | 28.65 m. |
| Breadth moulded | 12.00 m. |
| Depth | 5.40 m. |
| Draught to skegs | 5.90 m. |
| Draught to keel | 3.20 m. |
| Bollard pull | 70 Tons. |

Complement 7 persons

Fuel Oil Tanks 1 75 m³

PROPULSION

3 main engines 2000 BHP, 3 Schottel Rudderpropeller (2 Fwd., 1 aft)



FREIRE
SHIPYARD

OHSAS 18001

BUREAU VERITAS
Certification



ISO 9001

BUREAU VERITAS
Certification



ISO 14001

BUREAU VERITAS
Certification

